

Key	Default	Values	Description
DebuggingEnabled	0	0, 1	Disable (0) or Enable (1) debug logging. Log files are written per default to the my documents folder of the user.
DebugPath	(empty)		Override path for logging.
DefaultLanguage	en	en, nl, de, fr, sp	Override the default language (default fall back is English)
DisableSettings	0	0, 1	Disable (0) or Enable (1) the Disable settings function.
ExternalMails	(empty)	@domain.com;specific@domain.com	Exclude the interception of mail with InterceptMode in case one of these domains or specific email addresses are listed. Format is (without quotes) '@wildcard.com;@example.com;specific@example.com;specific2@example.com'.
GuestAccountsEnabled	0	0, 1	Enable the Guest account functionality. Guest accounts are created in Nextcloud if the Guest server app is enabled.
GuestAccountsEnforced	0	0, 1	Enforce the creation of Guest accounts. Note: in case Guest account creation is enforced, but the setting guestaccountsenabled is disabled, the last setting will be overridden.
HtmlSnippetPublicShare	{URL} {PASSWORD} {EXPIRATIONDATE}	<html>	Html for Public share. {URL} = Url, {PASSWORD} = Password, {EXPIRATIONDATE} = Expiration date
HtmlSnippetSecureMail	{URL} {PASSWORD} {EXPIRATIONDATE}	<html>	Html for Secure Mail. {URL} = Url, {PASSWORD} = Password, {EXPIRATIONDATE} = Expiration date
HtmlSnippetUploadFiles	{URL} {PASSWORD} {EXPIRATIONDATE}	<html>	Html for Uploading files. {URL} = Url, {PASSWORD} = Password, {EXPIRATIONDATE} = Expiration date
HtmlSnippetPassword	{PASSWORD}	<html>	Html for password {PASSWORD} = Password
InsertAtCurserEnabled	1	0, 1	Disable (0) or Enable (1), insert the HTML snippet at cursor.
InterceptMode	Off	Off, MaximumAttachmentSize, Ask	MaximumAttachmentSize = In case the attached attachments to the email exceed the set threshold, all the attachments will be uploaded to Nextcloud.
InterMails	(empty)		Exclude the interception of mail with InterceptMode in case one of these domains or specific email addresses is listed. Format is (without quotes) '@wildcard.com;@example.com;specific@example.com;specific2@example.com'.
Password	*	<hash>	Hashed user-password.
PasswordDialog	Off	Off, Before, BeforeAndAfter	Before = prompt the user with setting a password, BeforeAndAfter = prompt the user with setting a password and it is shown after the upload.
PathPublicShare	/Outlook/PublicShare/	<path>	Path to upload default files to for public shares.
PathSecureMail	/Outlook/SecureMail/	<path>	Path to upload default files to for secure mail.
PathUploadFiles	/Outlook/UploadFiles/	<path>	Path to upload default files to for uploading files.
SecureMailEnabled	0	0, 1	Disable (0) or Enable (1). Enables the user to mark their e-mail as 'secure mail' and upload the mail body to Nextcloud itself. The original mail contents will be replaced with a link to visit Nextcloud.
SecureMailEnforced	0	0, 1	Enforce the Secure Mail functionality for every mail. In case Secure Mail is disabled, but this setting is enforced, all the mails will be regarded as Secure Mail.
SendMode	CurrentMail or Separate		CurrentMail = include the password in the email body, Separate = send the password in a separate email.
ServerAppEnabled	0	0, 1	Disable (0) or Enable (1). This setting indicates if the add-in can retrieve the client settings from the server-app on the Nextcloud server. This will override ADMX settings if enabled!
Status	First	First, LoggedIn, Error, Ignore	Indicates the status of the add-in. In case some user does not need to use the add-in, use the value 'Ignore' (without quotes).
Threshold	0	0, 1	Threshold for InterceptMode (MaximumAttachmentSize) expressed in MB's. In case it is 0, all the email attachments will be uploaded.
Url	https://example.nextcloud.com/	<url>	The URL to your Nextcloud server. Please make sure it ends with a '/' (without quotes).
UserId	(empty)	(empty)	Not used.
Username	*	<username>	Username of the user.